



手柄運轉軌跡






接線定義		
PIN #	WIRE COLOR	DESCRIPTION
1	RED	POWER (+5V)
2	BLACK	GROUND
3	YELLOW	X OUT1 SENSOR
4	GREEN	X OUT2 SENSOR

技術參數:

1. 二軸 (X+Y) 霍爾傳感器
2. 彈簧自動回位
3. 操作角度: $\pm 18^\circ$
4. 操作力度: 0~3N (允許極限操作力: 15N)
5. 輸出電壓: $(0.5 \pm 0.1)V_{dc} \sim (2.5 \pm 0.1)V_{dc} \sim (4.5 \pm 0.1)V_{dc}$
6. 供電方式: $(5 \pm 0.1)V_{dc}$
7. 電源電流: $< 100mA$
8. 中心精度: $2.5V \pm 1\%$
9. 操作壽命: > 100 萬次
10. 防護等級: 面板以上 IP67
11. 工作溫度: $-40 \sim +70^\circ C$
12. 存儲溫度: $-45 \sim +80^\circ C$
13. LIMITER OPTION: SQUARE(□)



面板開孔尺寸



未指定容許±尺寸之公差		MTL	SPEC	DISPOSAL	福哥興業股份有限公司 FAVOR UNION CO., LTD.		
10以下	±0.3	△			UNIT	SCALE	TITLE
10~100	±0.5	△			MM		
100以上	±0.8	△			DRAWN	DESIGN	CHECK
角度	±5°	△			Nick	黃	APPROVAL
		DEVISION	DATE	DESIGN	2023/03/24	2023/03/24	DWG NAME
							DWG NO.