



P.C.MOUNTING

MECHANICAL LIFE: 30,000 make-and-break cycles.  
 CONTACT RESISTANCE: 10 mΩ max. initial @ 2-4VDC  
 100mA for both silver and gold plated contacts.  
 INSULATION RESISTANCE: 1,000 MΩ min.  
 DIELECTRIC STRENGTH: 1,000 Vrms min. @sea level.  
 OPERATING TEMPERATURE: -40°C to 85°C.

SWITCH FUNCTION			
Model No.	POS.1	POS.2	POS.3
ON/OFF	ON	NONE	ON
Term. Comm.	2-1	N/A	2-3
SCHEMATIC			

福哥興業股份有限公司 FAVOR UNION CO., LTD.

台灣新北市新莊區大安路20號

NO. 20 TA AN RD. HSIN CHUANG  
 NEW TAIPEI CITY TAIWAN R. O. C

TEL 886-2-2202-8766

FAX 886-2-2204-3500

比例 SCALE	品名 TITLE
單位 DIMENSION mm	SLIDE SWITCH SERIES
DO NOT SCALE DRAWING TOLERANCES UNLESS OTHERWISE	型號 MODEL
UP TO 10 ±0.3	FSS13-1-2-102-DE
ABOVE 10 TO 100 ±0.5	繪圖 DRAWN
ABOVE 100 ±0.8	許麒弘
ANGULAR DIMENSIONS 5°	核准 APPROVED
	黃威翔
	版次 REVISION
	A
	日期 DATE
	2019/8/13

繪圖 DRAWN	許麒弘	核准 APPROVED	黃威翔
	版次 REVISION	A	日期 DATE
			2019/8/13