



SOLDER LUG

MECHANICAL LIFE: 30,000 make-and-break cycles.
 CONTACT RESISTANCE: 10 mΩ max. initial @ 2-4VDC
 100mA for both silver and gold plated contacts.
 INSULATION RESISTANCE: 1,000 MΩ min.
 DIELECTRIC STRENGTH: 1,000 Vrms min.@sea level.
 OPERATING TEMPERATURE: -30°C to 85°C

SWITCH FUNCTION			
Model No.	POS.1	POS.2	POS.3
ON/OFF	ON	NONE	ON
Term. Comm.	2-1	OPEN	2-3
SCHEMATIC			

福哥興業股份有限公司 FAVOR UNION CO., LTD.

台灣新北市新莊區大安路20號

NO. 20 TA AN RD. HSIN CHUANG
 NEW TAIPEI CITY TAIWAN R. O. C

TEL 886-2-2202-8766

FAX 886-2-2204-3500

比例 SCALE		品名 TITLE		SLIDE SWITCH SERIES	
單位 DIMENSION mm		型號 MODEL		FSS13-1-2-201-DE	
DO NOT SCALE DRAWING TOLERANCES UNLESS OTHERWISE		繪圖 DRAWN		核准 APPROVED	
UP TO 10	±0.3	許麒弘		黃威翔	
ABOVE 10 TO 100	±0.5	DRAWN		核次 REVISION	
ABOVE 100	±0.8	REVISED		A	
ANGULAR DIMENSIONS	5 °	日期 DATE		2019/8/13	