



SPECIFICATIONS

CONTACT RATING: Max 0.4 VA max @ 48 VAC or DC

MECHANICAL LIFE: minimum 40,000 operations.

CONTACT RESISTANCE: 50mΩ max.

INSULATION RESISTANCE: 500MΩ at 250 VDC

DIELECTRIC STRENGTH: 500V, 50 Hz for the duration of 1 minute.

OPERATING TEMPERATURE: -20°C to 80°C.

DEGREE OF PROTECTION: IP67

SWITCH FUNCTION			
Model No.	POS.1	POS.2	POS.3
ON/OFF	ON	NONE	ON
Term. Comm.	2-1	N/A	2-3
SCHEMATIC		N/A	

福哥興業股份有限公司 FAVOR UNION CO., LTD.

台灣新北市新莊區大安路20號

NO. 20 TA AN RD. HSIN CHUANG
NEW TAIPEI CITY TAIWAN R. O. C

TEL 886-2-2202-8766

FAX 886-2-2204-3500

比例 SCALE	品名 TITLE	SLIDE SWITCH SERIES		
單位 DIMENSION mm	型號 MODEL	FSS95-1-2-201-DE		
DO NOT SCALE DRAWING TOLERANCES UNLESS OTHERWISE	繪圖 DRAWN	許麒弘	核准 APPROVED	黃威翔
UP TO 10 ±0.3		版次 REVISION	A	日期 DATE
ABOVE 10 TO 100 ±0.5				2019/8/14
ABOVE 100 ±0.8				
ANGULAR DIMENSIONS 5°				

繪圖 DRAWN	許麒弘	核准 APPROVED	黃威翔
版次 REVISION	A	日期 DATE	2019/8/14