



P.C.MOUNTING

SPECIFICATIONS

MECHANICAL LIFE: 40,000 make-and-break cycles.
 CONTACT RATING: 0.4 VA max. @ 20 V AC or DC max.
 CONTACT RESISTANCE: Below 100 m Ω typ. initial @ 2-4 V DC, 100 mA.
 INSULATION RESISTANCE: 500 M Ω min.
 DIELECTRIC STRENGTH: 500 Vrms min. @ sea level.
 OPERATING TEMPERATURE: -30°C to 85°C

SWITCH FUNCTION		
	POS.1	POS.2
Model No.		
ON/OFF	ON	ON
Term. Comm.	5-6	5-4
SCHEMATIC		

福哥興業股份有限公司 FAVOR UNION CO., LTD.

台灣新北市新莊區大安路20號

NO. 20 TA AN RD. HSIN CHUANG
 NEW TAIPEI CITY TAIWAN R. O. C

TEL 886-2-2202-8766

FAX 886-2-2204-3500

比例 SCALE		品名 TITLE		SLIDE SWITCH SERIES	
單位 DIMENSION mm		型號 MODEL		FSX07-1-2-V01-DE	
DO NOT SCALE DRAWING TOLERANCES UNLESS OTHERWISE		繪圖 DRAWN	許麒弘	核准 APPROVED	黃威翔
UP TO 10 ±0.3					
ABOVE 10 TO 100 ±0.5		日期 DATE	版次 REVISION	A	2019/8/7
ABOVE 100 ±0.8					
ANGULAR DIMENSIONS 5°					