



SPECIFICATIONS

MECHANICAL LIFE: 40,000 make-and-break cycles.
 CONTACT RATING: 0.4 VA max. @ 20 V AC or DC max.
 CONTACT RESISTANCE: Below 100 mΩ typ. initial @ 2-4 V DC, 100 mA.
 INSULATION RESISTANCE: 500 MΩ min.
 DIELECTRIC STRENGTH: 500 Vrms min.@sea level.
 OPERATING TEMPERATURE: -30°C to 85°C.

SWITCH FUNCTION			
Model No.	POS.1	POS.2	POS.3
ON/OFF	ON	NONE	ON
Term. Comm.	5-6	N/A	5-4
SCHMATIC			

福哥興業股份有限公司 FAVOR UNION CO., LTD.

台灣新北市新莊區大安路20號

NO. 20 TA AN RD. HSIN CHUANG
 NEW TAIPEI CITY TAIWAN R. O. C

TEL 886-2-2202-8766

FAX 886-2-2204-3500

比例 SCALE	品名 TITLE	TOGGLE SWITCH SERIES		
單位 DIMENSION mm	型號 MODEL	FSY07-1-2-H01-DE		
DO NOT SCALE DRAWING TOLERANCES UNLESS OTHERWISE	繪圖 DRAWN	許麒弘	核准 APPROVED	黃威翔
UP TO 10 ±0.3			版次 REVISION	日期 DATE
ABOVE 10 TO 100 ±0.5			A	2019/8/16
ABOVE 100 ±0.8				
ANGULAR DIMENSIONS 5°				

繪圖 DRAWN	許麒弘	核准 APPROVED	黃威翔
		版次 REVISION	日期 DATE
		A	2019/8/16