



P.C.MOUNTING

SPECIFICATIONS

MECHANICAL LIFE: 40,000 make-and-break cycles.
 CONTACT RATING: 0.4 VA max. @ 20 V AC or DC max.
 CONTACT RESISTANCE: Below 100 mΩ typ. initial @ 2-4 V DC, 100 mA.
 INSULATION RESISTANCE: 500 MΩ min.
 DIELECTRIC STRENGTH: 500 Vrms min.@sea level.
 OPERATING TEMPERATURE: -30°C to 85°C.
 DEGREE OF PROTECTON: IP67

SWITCH FUNCTION			
Model No.	POS.1	POS.2	POS.3
ON/OFF	ON	NONE	ON
Term. Comm.	5-6	N/A	5-4
SCHEMATIC			

福哥興業股份有限公司 FAVOR UNION CO., LTD.

台灣新北市新莊區大安路20號

NO. 20 TA AN RD. HSIN CHUANG
 NEW TAIPEI CITY TAIWAN R. O. C

TEL 886-2-2202-8766

FAX 886-2-2204-3500

比例 SCALE		品名 TITLE		TOGGLE SWITCH SERIES	
單位 DIMENSION mm		型號 MODEL		FSY07-1-2-V01-DE	
DO NOT SCALE DRAWING TOLERANCES UNLESS OTHERWISE		繪圖 DRAWN		核准 APPROVED	
UP TO 10	±0.3	許麒弘		黃威翔	
ABOVE 10 TO 100	±0.5	DRAWN		核版	
ABOVE 100	±0.8	DRAWN		REVISION	
ANGULAR DIMENSIONS	5 °	DRAWN		A	
		日期 DATE		2019/8/16	